

The solid Keulmac conveyor is suitable for many applications.
For example for transporting potatoes, onions, fertilizer or for filling boxes.



Because this Keulmac conveyor is standard equipped with a kink and an electronic/hydraulic unit, this machine is suitable for, planting work on the land or for storage work on the farm.

The bottom unloading belt is provided with a trough-shaped rubber belt with high carriers, which are supported by v-shaped rollers. The speed of the belt is infinitely adjustable.

It is also possible to equip the bottom unloader with wireless control. This allows the machine to be fully operated from the tractor cabin. This makes working in dusty locations a struggle of the past.

Specifications conveyor

- all types of conveyor belts are supplied with an electric/hydraulic drive as standard
 - the belt is driven by a hydraulic motor and the speed of the belt is infinitely variable
 - the conveyor can be hydraulically adjusted in height
 - the conveyors with a belt width of 65 cm. can optionally be hydraulically swaying
- This is standard with a belt width of 80 cm.

Available in belt length:	3.50 meters	4.00 meters	4.50 meters	5.00 meters	5.50 meters	6.00 meters	6.50 meters
Belt width:	65 cm.	65 cm.	65 or 80 cm.	65 or 80 cm.	65 or 80 cm.	65 or 80 cm.	65 or 80 cm.
Track width:	1.50 meters	1.50 meters	1.50m. with 65cm. belt & 1.80-2.00m. adjustable with 80cm. belt	1.50m. with 65cm. belt & 1.80-2.00m. adjustable with 80cm. belt	1.50m. with 65cm. belt & 1.80-2.00m. adjustable with 80cm. belt	1.50m. with 65cm. belt & 1.80-2.00m. adjustable with 80cm. belt	1.50m. with 65cm. belt & 1.80-2.00m. adjustable with 80cm. belt
Elektr./hydr. unit:	2.2 KW	2.2 KW	2.2KW with 65cm. & 4KW with 80cm. belt	2.2KW with 65cm. & 4KW with 80cm. belt	4KW with 65cm. & 80cm. belt	4KW with 65cm. & 5.5KW with 80cm. belt	4KW with 65cm. & 5.5KW with 80cm. belt
Dump height with fixed kink horizontal:	1,70 meters	1,85 meters	2,00 meters	2,30 meters	2,70 meters	2,90 meters	3,10 meters

Options conveyor

more price:

- fall breaker automatic 2 chutes (for 65 and 80 cm. belt)
- preparation for fall breaker automatic 2 chutes (for 65cm. belt)
- hydraulic moveable (for 65 cm. belt)
- 10.0/75-15.3 tires (for sizes 350-400-450-500 / 65)
- remote control with 1 hand transmitter wireless
- second remote control for hand transmitter
- hose set 2 x 10m.
- road lightning led
- three-way tap (on-off)
- hydraulic support leg

lower price:

- straight version without bend
- only electric or only hydraulic powered

if only with electric drive:

- frequency control
- hydraulic height adjustment by handpomp



Call **(0031-527 25 33 04)**, mail **(info@keulmac.nl)**
or visit the website **(www.keulmac.nl)**
for more information!

