

Box-tilt trailer

The Keulmac box-tilt trailer is a robust, high quality box trailer for harvesting.



This trailer consists of a strong lower frame on a tandem axle, with hydraulically movable tilting cage mounted on it. This minimizes the height of the fall and the risk of product damage. Partly due to the low construction of the lower frame in combination with wide low-pressure tires, the driver has a perfect view of the filling of the boxes.

Due to a unique construction, the top of the box remains in the same line with respect to the harvester when the cage is tilted. This gives the driver of the harvester and wagon peace of mind. In addition, it also makes it easier to fill the box. This vehicle is standard equipped with a hydraulic valve and LED road lighting.

Specifications box-tilt trailer

- available in lengths: 4 x 1.60m. / 5 x 1.60m. / 6 x 1.60m.
- standard tyres: 400-60-15.5 / 620-40-22.5 / 620-40-22.5
- length: 8.60m. / 10.40m. / 12.00m.
- load floor height: 0.90m. / 1.10m. / 1.10m.
- standard box size: 1.60 x 1.25m. (different on request)
- track width: 1.50m. for 4 x 1.60, 1.80m. for 5 x 1.60 en 6 x 1.60 (different on request)
- pull boom: equipped with rotating drawbar eye
- wheels: tandem in two fixed axles

Options box-tilt trailer

- air-operated brakes
- braked axles
- choice of various tyres



Call **(0031-527 25 33 04)**, mail **(info@keulmac.nl)**
or visit the website **(www.keulmac.nl)**
for more information!

